



KCC PAINT **SUPRO** **WATERPROOF**

This is a one-component water-soluble, environmentally friendly waterproofing material that can be painted easily.

KCC PAINT

SUPRO WATERPROOF



Recommended Use

Exterior wall and other parts of waterproofing materials
(Concrete, Cement mortar)



Theoretical Coverage

5.26 m²/kg (80 μm)

► Actual requirements may vary depending on film thickness and aspiration.



Colors

Green, Gray (matt)



D.F.T (Dry Film Thickness)

80 μm (1~2 times painting)



Packing Unit

17 kg, 4 kg



Method

Brush, Roller, Spray



Recoating Interval

		10 °C	20 °C	30 °C
Recoating Time (hours)	Minimum	8	4	1
	Maximum	24	24	24

※ If you have any questions about products or you want to know safety information, you can get the technical datasheets and MSDS on our Internet Homepage (www.kccworld.co.kr) or ask the customer's service.



Corporate Headquarters

344, Sapyeong-daero, Seocho-gu,
Seoul, Korea
Tel : (82)-2-3480-5000
Fax : (82)-2-3480-5436
e-mail : w3master@kccworld.co.kr

KCV Hochimin Office.

Room 4, 12th Floor, Pearl Plaza, 561
Dien Bien Phu Str., Ward 25, Binh Thanh
Dist., HCMC, Vietnam
Tel : (84)-8-6269-0305
e-mail : cjh9871@kccworld.co.kr

KCC (Hanoi) Hanoi Office.

VINACONEX 9 TOWER AT PHAM HUNG
ROAD, ME TRI - TU LIEM-HA NOI
(10 floor)
Tel : (84)-4-3787-8647
e-mail : crekim@kccworld.co.kr